

MDM (Multi-Display Manager)



[MDM-10V-M5-1-D]

Input Interface	HDMI	HDMI 1.4 x6
	DVI	DVI-D x1 DVI-A x1
	VGA	D-sub x1
	Total	9
	Total Max Bandwidth	8MP
Output Interface	DP	DP 1.4 x3
	HDMI	HDMI 2.0 x1
	DVI	DVI-D x1
	Total Max Bandwidth	8MP x2 and 4MP x1 and 2MP x1
Module (Either one)	keyboard & Mouse Switch	7 port USB Type-B (Option)
	Power Breakout Board	7 port 5V (Option)
Features	Frames Delay	2~3 Frames
	Scaling Down/Up	Yes
	Administration	Web-Browser
	Remote Control	Network
	Support Touch Control	Yes
	Support Keyboard	Yes
	Support Mouse	Yes
	Image Mirror	Yes
	Layouts	1000
Power Requirements	Input Voltage(V)	AC 90~264
	Power Consumption(W)	340(typ.)
	Redundant Power	Yes
Physical Characteristics	Chassis	19" 4U
	Dimensions (W×H×D) (mm)	483x177x450mm
	Weight (kg)	20 (Typ.)
Reliability	Operating Temperature (°C)	5 to 40
	Operating Humidity (RH)	10% to 80%
	Storage Temperature (°C)	-40 to 70
	Storage Humidity (RH)	10% to 95%
Certifications and Compliances		UL 60950, CE, FCC, RoHS, WEEE

MDM (Multi-Display Manager)



[MDM-10V-M7-1-D]

Input Interface	HDMI	HDMI 2.0 x1 HDMI 1.4 x8
	DVI	N/A
	VGA	N/A
	Total	9
	Total Max Bandwidth	18MP
Output Interface	DP	DP 1.4 x3
	HDMI	HDMI 2.0 x1
	DVI	DVI-D x1
	Total Max Bandwidth	8MP x2 and 4MP x1 and 2MP x1
Module (Either one)	keyboard & Mouse Switch	7 port USB Type-B (Option)
	Power Breakout Board	7 port 5V (Option)
Features	Frames Delay	2~3 Frames
	Scaling Down/Up	Yes
	Administration	Web-Browser
	Remote Control	Network
	Support Touch Control	Yes
	Support Keyboard	Yes
	Support Mouse	Yes
	Image Mirror	Yes
	Layouts	1000
Power Requirements	Input Voltage(V)	AC 90~264
	Power Consumption(W)	340(typ.)
	Redundant Power	Yes
Physical Characteristics	Chassis	19" 4U
	Dimensions (W×H×D) (mm)	483x177x450mm
	Weight (kg)	20 (Typ.)
Reliability	Operating Temperature (°C)	5 to 40
	Operating Humidity (RH)	10% to 80%
	Storage Temperature (°C)	-40 to 70
	Storage Humidity (RH)	10% to 95%
Certifications and Compliances		UL 60950, CE, FCC, RoHS, WEEE